

GP Cleaner

Revision: 14/10/2020

Page 1 from 1

Technical data

Basis	Water with specific detergents
Consistency	Fluid
Density**	1,00 g/ml
Application temperature	5 °C → 35 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Soudal GP Cleaner is a General Purpose, all-round, professional cleaner for removing all kinds of stubborn dirt such as, oil, grease, etc. Suitable for most surfaces, materials and textiles.

Properties

- Biodegradable
- Ready for use
- Not flammable
- Multi-purpose use
- Excellent cleaning properties
- Does not contain harmful solvents nor acids
- Mildly alkaline (pH: 9.5) for effective cleaning

Applications

- Cleaning and degreasing of subfloors and materials.
- Where the use of a non-hazardous, solvent free cleaner is required.
- Removes all kinds of dirt such as oil, grease, cleaning detergents and wax in a safe manner.
- Degrease and clean surfaces before sealing as on PVC, metal and aluminum.
- Smoothing of joints created with most common types of sealants (silicones, polyurethane and MS polymers).

Packaging

Colour: green

Packaging: 1 L bottle

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Application method

Application method: Spray GP Cleaner at the heavily polluted parts. Let the foam layer work for a few minutes. Stubborn dirt or mud can possibly be rubbed off with a sponge. Then thoroughly rinse off with plenty of water and dry with a dry cloth or blow dry.

Health- and Safety Recommendations

Take the usual labour hygiene into account.

Remarks

- GP Cleaner is slightly alkaline.
- We strongly recommend not to apply the product in full sunlight as it will dry very fast.
- Rinse surfaces with water after cleaning to avoid stains.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.