



Cockpit Cleaner

Revision: 8/03/2022 Page 1 from 1

Technical data

Basis	Waterbased cleaning foam
Consistency	Fluid
Application temperature	$5 ^{\circ}\text{C} \rightarrow 35 ^{\circ}\text{C}$

^{*} These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

High-end cockpit foamspray for cleaning the dashboard and the complete interior in cars.

Properties

- Cleans
- · Leaves no residue
- Absorbs organic dirt
- · Gentle on all surfaces

Applications

- This foamcleaner has excellent soft and cleaning properties on plastics and other materials used in interiors of cars.
- Removes stains resulting from organic substances.

Packaging

Colour: Transparent Packaging: 400 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Substrates: Plastics, textile fabrics, metals, glass, rubbers, leather

Application method

Application method: Apply the foamcleaner directly on the surface. Wipe off the foam as soon as the absorbed dirt appears on the surface.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Dangerous. Respect the precautions for use.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

 Soudal NV
 Everdongenlaan 18 - 20
 B-2300 Turnhout, Belgium

 Tel: +32 (0)14-42.42.31
 Fax: +32 (0)14-42.65.14
 www.soudal.com